






Documentelligence[™]: Innovative Solutions, Services & Support

thermal facial recognition





How is facial recognition handled?

Documentelligence™ Temperature & Facial Recognition compares your image with the face database stored locally in the device. With the Bioassay feature, it can differentiate between a live face (living body) and a photo and denies access if someone tries to scan a photo. It recognizes faces even when the person is wearing a protective mass and supports 1:1 and N:1 facial recognition algorithm for higher accuracy. Facial recognition can be completed against a face database of 30,000 people in one second.

What is the accuracy of the facial recognition scan?

The 1:1 comparison recognition rate is more than 99.7%, and the live detection accuracy rate is 98.3%. Face recognition pass speed is less than 1 second. It supports accurate face recognition and comparison while wearing mask.

Is it intelligent enough to differentiate between other hot objects such as a "hot cup of coffee" and a fever?

It will only scan faces and not other objects. However, if you are holding a hot cup of coffee near your face, the thermal scanner reading will not correct as the temperature in front of the face is going to be elevated.

Is it possible to add ID card & fingerprint scanners?

Yes, add optional peripherals including ID card & fingerprint scanners. Match faces with the ID Card and fingerprints to improve accuracy. Other peripherals also supported including IC card reader & two-dimensional code reader.

Does Documentelligence™ Temperature & Facial Recognition connect with doors, gates, peripheral devices & network?

Industrial standard interfaces (Wiegand, Relay, RS-232) for controlling doors and gates. USB interfaces for connecting peripheral devices and firmware updates. Ethernet and Wi-Fi connection for network management.



Connect with doors, gates, peripheral devices & network

Does it sound an alarm when a person with fever is detected?

Yes. An alarm rings upon elevated temperature detection alongside the lights blinking red. With the alert OFF it says "Abnormal temperature + red light" in a friendly voice.

What secure data is stored on the device and is it secure?

Documentelligence™ Temperature & Facial Recognition is a screening device and can be used in offline mode without connecting it to any network. GoSafe stores pictures at time of entry of employees that were recognized. It can also store pictures of strangers if the setting for capturing strangers is enabled. It also stores the temperature at time of entry, the date and time of entry and employee ID.



One Documentelligence™ Temperature & Facial Recognition can scan approximately 15 people per minute assuming they stand at least 6 feet apart. You can determine how many units you need based on the rate at which the employees enter at the facilities entry points over a given period of time.



Will Documentelligence™ Temperature & Facial Recognition detect if a face mask is being worn?

Yes, it detects if a protective mask is being worn. You can select the additional protection to deny entry if the person is not wearing a mask. The light will also blink red and the device will ask user to wear a mask in order to be granted access.

Is Documentelligence™ Temperature & Facial Recognition a hands-free operation?

Yes, its embedded thermal & face recognition sensors provide 100% hands-free user authentication.





SPECIFICATIONS			
Screen		Serial Communication	1 RS232 serial port
Size	8.0" IPS LCD screen	Relay Output	1 door open signal output
Resolution	800x1280	Wiegand	1 Wiegand 26/34 output and input
Design	Industrial-grade, waterproof, dustproof & vandal-proof	Upgrade Button	Supports USB boot upgrade button
Processor		Access Control	
CPU	Qualcomm Snapdragon Octa-Core Processor	Facial Recognition based Access Control	1:1 & N:1 face recognition
CPU (Optional)	Rockchip RK3288 Quad-Core	Face Mask Detection based Access	Available
System	Android 7.1.2	Control	
Storage	EMMC 8 GB	Elevated Temperature based Access Control	Available
Camera		ID Card based Access Control	Optional IC card, S50, NTAG, CPU, DESfire
Resolution	2 million pixels	Barcode Reader based Access Control	Optional Barcode, 2D Barcode & QR Code R
Туре	Binocular vision wide dynamic camera	Call Receptionist / Security to Grant Access	Available
Aperture	F2.4	Call IT / Screen Skills Guru for Support	Available
Focusing Distance	19.6"– 60"	Face Library	Up to 30,000
White Balance	Auto	,	
Photo Flood Light	LED and IR dual photo flood light	Remote Management	
Infrared Thermal Imaging Module		Attendance Tracking & Reporting	Available
3 3		User Interface Customization	Available
Temperature Detection	Available	Remote Device Management	Available
Temperature Detection Distance	3.2' (optimal distance 1.6')	Remote Database Management	Available
Temperature Measurement Accuracy	≤ ±0.9 °F	Remote Firmware Upgrade	Available
Temperature Measurement Range	50 °F – 107.6 °F	System	
Thermal Field of View	89.6 x 89.6 °	Power	DC 12V
Elevated Temperature Alarm	Supported (temperature alarm value can be set)	Operating Temperature	0 °F – 140 °F
Interfaces		Power Consumption	13.5W Max
Network Module	Ethernet (RJ-45) and Wireless (Wi-Fi)	Installation Method	Wall Mount, Table Stand & Floor Stand
Audio	2.5W / 4R speakers	Product Size	11.66" x 5.23"x 0.98"
USB	1 USB OTG, 1USB HOST standard A port	What's in the Box	OneScreen GoSafe, Power Adapter, User Mo







COPIER FAX BUSINESS TECHNOLOGIES 465 Ellicott Street Buffalo, NY 14203 (716)853-5000

75 South Clinton, Suite 510 Rochester, NY 14604 (585)563-6757

CopierFaxBT.com