

Report Types

The following types of fax reports are available.

Report name	Description
Activity Report	This report contains results of sent and received faxes. A total of 700 jobs are recorded on separate pages for transmission and reception. By default, the report is automatically printed for every 100 communications. The activity report is automatically printed. When necessary, records containing only transmission or reception jobs can be printed manually on the [Job List] screen.
TX Result Report	This report contains the results of fax transmission. By default, the report is automatically printed when a transmission failure occurs.
Polling TX Report	This report contains polling transmission results. By default, the report is automatically printed when a polling transmission has failed.
Polling RX Report	This report contains results of polling reception. By default, the report is automatically printed when a polling reception has failed.
Sequential Polling RX Report	This report contains results of faxes received by polling from multiple destinations. By default, the report is automatically printed when faxes from multiple destinations are received by polling.
Broadcast Report	This report contains results of faxes sent by broadcast. By default, the report is automatically printed upon completion of the broadcast transmission.
Reservation Communication Report	This report contains records of reserved fax transmissions. By default, the report is automatically printed when a fax transmission is reserved.
Reservation Polling TX Report	This report contains records of reserved polling transmissions. By default, the report is automatically printed when a polling transmission is reserved.
Broadcast Reserved Report	This report contains records of reserved broadcast transmissions. By default, the report is automatically printed when a broadcast transmission is reserved.
An address Polling Rx Reserved Report	This report contains records of reservations on polling RX jobs for one address. By default, the report is automatically printed when a polling RX job is reserved from one address.
Sequence Polling Rx Reserved Report	This report contains records of reservation on polling RX jobs for multiple addresses. By default, the report is automatically printed when a polling RX job is reserved from multiple addresses.
Confidential RX Report	This report contains results of confidential faxes received. By default, the report is automatically printed when a confidential fax is received.

Bulletin TX Report	This report contains results of the transmission in polling RX of a file registered in a Bulletin Board User Box. By default, the report is automatically printed when a file registered in a Bulletin Board User Box is sent in conjunction with polling RX.
Relay TX Result Report	This report contains results of the transmission of a fax received by a relay station of the relay distribution to a distribution station. By default, the report is automatically printed when a fax is delivered to a distribution station.
Relay Request Report	This report contains results of the reception of a fax as a relay station of the relay distribution. By default, the report is automatically printed when a fax is received in the relay distribution.
Job Settings List	This list contains the details of [Fax Settings]. For details on the printing procedure, refer to Here .



Related setting (for the administrator)

 [Report Settings] ([Here](#))

[DPG]: Page separation sending
[MIX]: Transmission in mixed mode
[CALL]: Manual communication
[CSRC]: Remote diagnosis
[FWD]: Forward
[PC]: PC-FAX
[BND]: 2-sided bind direction
[SP]: Special original
[FCODE]: Specification of F code
[RTX]: Retransmission
[RLY]: Relay
[MBX]: Confidential
[BUL]: Bulletin board
[IPADR]: IP Address Fax
[I-FAX]: Internet Fax

[Result]

[OK]: Described when communication is ended normally.
[S-OK]: Described when communication is stopped.
[PW-OFF]: Described when the main power is turned off during communication.
[TEL]: Described when you get a phone call.
[NG]: Described when a communication error occurs.
[Cont]: Described when a communication error occurs and the machine shifts to the retransmission wait state (Error Page Redial).
[No Ans]: Described when no response is returned from the peer.
[Refuse]: Described when you get a phone call from a number registered in the call rejection service.
[Busy]: Described when communication failed because the peer was busy.
[M-Full]: Described when receiving failed because the fax file memory become full during receiving.
[LOVR]: Described when the length of the received page exceeds the maximum value. (IP address fax or Internet fax)
[POVR]: Receiving page over. Described when the number of received pages exceeds 3,000. (IP address fax or Internet fax)
[FIL]: File error. Described when the received file is not supported. (IP address fax or Internet fax)
[DC]: Decoding error. Described when the system failed to decode the received file. (IP address fax or Internet fax)
[MDN]: Described when an MDN response failed. (Internet Fax)
[DSN]: Described when a DSN response failed. (Internet Fax)
[PRINT]: Described when a document saved by the Memory RX function is printed.
[DEL]: Described when a document saved by the Memory RX function is deleted.

[SEND]: Described when a document saved by the Memory RX function is sent.